| Cloud Gateways Switching WiFi | Camera Security Door Access | New Integrations Accessory Tech | Identity | Support Store (2) |
|---|------------------------------------|--------------------------------------|---|-------------------|
| UniFi UISP Branding Q Search | h UniFi products | | | |
| UniFi Cloud Gateways Swit | | era Security Door Access Cloud | dKeys & Gateways Power Tech New Integration | s Accessories |
| ofessional Max > Pro Max 24 | | | | |
| Pro Max 24 USW-Pro-Max-24 | Datasheet | In The Box Marketing Images | Installation Guide | |
| | Dutusheet | in the box indicating indges | | |
| | | Mechanical | | |
| 1.3° touchscreen (16) GbE with AR switch management RJ45 ports | (8) 2.5 GbE RJ45 ports | Dimensions | 442 x 325 x 44 mm (17.4 x 12.8 x 1.7") | |
| | | Weight | Without mounting brackets: 4.2 kg (9.3 lb) With mounting brackets: 4.3 kg (9.5 lb) | |
| DC power backup* Layer 3 switching features | (2) 10G SFP+ Reset ports button | Enclosure material | SGCC steel | |
| | | Hardware | | |
| |) Power input | Management interface | Ethernet In-Band | |
| (24) Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network** | | Networking interface | (16) GbE RJ45 ports (8) 1/2.5 GbE RJ45 ports | |
| | , 43.7 mm | Total non-blocking throughput | (2) 10G SFP+ ports 56 Gbps | |
| 442.4 mm | 325 mm | Switching capacity | 112 Gbps | |
| | | Forwarding rate | 83.328 Mpps | |
| | - C. C. | Power method | (1) Universal input, 100—240V AC, 50/60 Hz (1) USP-RPS DC input | |
| | | Power supply | AC/DC, internal, 50W | |
| Cloud Gateway | | Supported voltage range | 100—240V AC | |
| Pro Max 24 | | Max. power consumption | 50W | |
| Power Backup Power Backup | | LCM display | (1) 1.3" touchscreen | |
| | | Button Ambient operating temperature | Factory reset | |



Ambient operating temperature -5 to 40° C (23 to 104° F) Ambient operating humidity 10 to 90% noncondensing CE, FCC, IC Certifications

Switching Features

| Layer 2 features | IGMP snooping | | |
|------------------|--|--|--|
| | STP / RSTP with priorities and port-level disable | | |
| | Port isolation | | |
| | Storm control | | |
| | Voice VLAN | | |
| | Port mirroring | | |
| | LACP port aggregation | | |
| | Multicast / broadcast rate limiting | | |
| | MAC address blocking | | |
| | Flow control | | |
| | 802.1X control | | |
| | Jumbo frames | | |
| | Proprietary loop protection | | |
| | DHCP snooping / guarding | | |
| | Egress rate limit | | |
| | LLDP-MED | | |
| | Port restricted by MAC | | |
| | Device isolation with ACLs | | |
| Layer 3 features | DHCP for locally-managed networks | | |
| | DHCP relay | | |
| | Inter-VLAN routing between networks on same switch | | |
| | Static routing between local networks | | |
| | Network isolation with ACLs | | |
| Etherlighting™ | | | |
| Ethernet | Locating | | |
| | Speed/link | | |
| | Native VLAN/network | | |
| SFP+ | Locating | | |
| | Speed/link | | |
| | Native VLAN/network | | |
| | | | |
| | | | |
| LEDs | | | |
| LEDs System | Status | | |

Application Requirements

UniFi Network

Version 8.0.24 and later

Buy Now Company Training Tools Ubiquiti Store WiFiman Careers Courses Contact Us Find a Distributor UISP Calendar Become a Distributor UniFi Design Center X UISP Design Center By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts. Downloads

f

<u>Cookies Settings</u>

Subscribe

Accept All Cookies

X D O

Email



Terms of Service | Privacy Policy | Legal | Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.

X

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.

