

#### Mechanical

**Dimensions** 442 x 325 x 44 mm (17.4 x 12.8 x 1.7") Weight Without mounting brackets: 4.8 kg (10.6 lb) With mounting brackets: 4.9 kg (10.8 lb)

**Enclosure material** SGCC steel

#### Hardware

Management interface Ethernet In-Band Networking interface (32) GbE RJ45 ports (16) 1/2.5 GbE RJ45 ports (4) 10G SFP+ ports

Total non-blocking throughput 112 Gbps Switching capacity 224 Gbps Forwarding rate 166.656 Mpps

Power method (1) Universal input, 100—240V AC, 50/60 Hz

AC/DC, internal, 100W

(1) USP-RPS DC input

(1) 1.3" touchscreen

**Power supply** Supported voltage range 100-240V AC Max. power consumption 100W

**Button** Factory reset

-5 to 40° C (23 to 104° F) Ambient operating temperature Ambient operating humidity 10 to 90% noncondensing

Certifications CE, FCC, IC

#### **Switching Features**

LCM display

Layer 2 features IGMP snooping

STP / RSTP with priorities and port-level disable Port isolation

Storm control Voice VLAN Port mirroring LACP port aggregation Multicast / broadcast rate limiting MAC address blocking Flow control

802.1X control Jumbo frames Proprietary loop protection DHCP snooping / guarding Egress rate limit LLDP-MED Port restricted by MAC

Device isolation with ACLs

Layer 3 features DHCP for locally-managed networks

DHCP relay

Inter-VLAN routing between networks on same switch

Static routing between local networks Network isolation with ACLs

# Etherlighting™

**Ethernet** Locating

Speed/link Native VLAN/network

SFP+ Locating Speed/link


Native VLAN/network

# **LEDs**

System Status **RPS** Status

# **Application Requirements**

**UniFi Network** Version 8.0.24 and later



Terms of Service | Privacy Policy | Legal | Cookies Settings

© 2024 Ubiquiti, Inc. All rights reserved.

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.

Cookies Settings

X