



Switching / Professional Max & XG Pro XG 48 PoE



Overview

Dimensions	442 x 480 x 44 mm (17.4 x 18.9 x 1.7")
Port Layout	
— 2.5 GbE RJ45	16 (All PoE+++) (2.5G/1G/100M/10M)
— 10 GbE RJ45	32 (All PoE+++) (10G/5G/2.5G/1G/100M/10M)
— 25G SFP28	4 (25G/10G/1G)
Max. PoE Output	Up to PoE+++
Total PoE Availability	200-240V AC: 1080W 100-120V AC: 972W
Redundancy	DC Power Backup
Layer 3	Yes
Form Factor	Rack mount (1U)
Etherlighting™	Yes

Performance

Switching Capacity	920 Gbps
Total Non-Blocking Throughput	460 Gbps
Forwarding Rate	684 Mpps
Supported VLANs	1,000
MAC Address Table Size	128,000
L3 Table Size	
ARP Entries	128,000
IPv4 Routes	256,000
Packet Buffer Size	8 MB

Layer 3 Features

DHCP Server (Local Networks)	Yes
DHCP Relay	Yes
Inter-VLAN Routing (Local Networks)	Yes
Static Routing (Local Networks)	Yes

Layer 2 Features

LACP Port Aggregation	Yes
STP & RSTP	Yes
QoS (DSCP)	Yes
Pro AV Profiles (Play, Dante, Q-SYS, NDI, SDVoE, Shure, AES67, Crestron)	Yes
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	Yes
IGMP Snooping	Yes
802.1X Control	Yes
MAC-Based ACLs & Device Isolation	Yes
DHCP Snooping & Guarding	Yes
Egress Rate Limit	Yes
Flow Control	Yes
Storm Control	Yes
Multicast & Broadcast Rate Limiting	Yes
MAC Address Blocking	Yes
IP-Based ACLs & Network Isolation	Yes
MAC-Based Port Restriction	Yes
Port Isolation	Yes
Port Mirroring	Yes
Jumbo Frames	Yes
LLDP-MED	Yes
Voice VLAN	Yes
Loop Protection	Yes

Hardware

PoE Ports

PoE+++	48
--------	----

Max. PoE Wattage per Port by PSE

PoE	15.4W
PoE+	30W
PoE++	60W
PoE+++	90W

Max. Power Consumption

200W (Excluding PoE Output)

200-240V: 1,280W /
100-120V AC: 1,172W (Including PoE Output)

Power Method

(1) Universal input, 100—240V AC, 50/60 Hz
(1) USP RPS DC input

Power Input Method

AC input

Power Supply

AC/DC, internal, 1,350W


Supported Voltage Range

100—240V AC


Management

Ethernet
AR

Weight	Without mounting brackets: 8.7 kg (15.4 lb) With mounting brackets: 8.8 kg (15.7 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	482.6 mm (19") four-post racks Posts depths ranging from 600 to 1,066 mm (23.6-42")
LCM Display	1.3" touchscreen
ESD/EMP Protection	Air: $\pm 30\text{kV}$, contact: $\pm 20\text{kV}$
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
Etherlighting™	
└ Ethernet	Yes
└ SFP28	Yes
LEDs	
└ RPS	Yes
Certifications	CE, FCC, IC
NDAA Compliant	Yes



*1,080W with 200-240V AC and 972W with 100-120V AC.
 **Require UniFi Power Backup.



***Pair with UniFi Etherlighting Patch Cables for optimal brightness.