



Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Max. Power Consumption	250W
Power Method	(1) Universal input, 100—240V AC, 50/60 Hz (1) USP RPS DC input
Power Input Method	AC input
Power Supply	AC/DC, internal, 300W
Supported Voltage Range	100—240V AC
Management	Ethernet AR
Weight	Without mounting brackets: 7.5 kg (16.5 lb) With mounting brackets: 7.6 kg (16.8 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	482.6 mm (19") four-post racks Posts depths ranging from 600 to 1,066 mm (23.6-42")
LCM Display	1.3" touchscreen
ESD Protection	Air: ± 30kV, contact: ± 14kV
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
Etherlighting™	
- SFP+	✓
QSFP28	✓
LEDs	
RPS	✓
NDAA Compliant	1
Certifications	CE, FCC, IC
∧ Software	
A li ti D i t	
Application Requirements	

Company **Buy Now** Training Tools Ubiquiti Store WiFiman Blog Courses Case Studies Find a Distributor UISP Calendar UniFi Design Center Trainers Become a Distributor UISP Design Center Trust Center Become a Trainer X Downloads By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts. Accept All Cookies Cookies Settings

Terms of Service | Privacy Policy | Legal | Cookies Settings

© 2025 Ubiquiti, Inc. All rights reserved.

ation,

X

Cookies Settings