



Switching / Flex Mini 2.5G  
**USW-FLEX-2.5G-5**



### Mechanical

Dimensions	117.1 x 90 x 21.2 mm (4.6 x 3.5 x 0.8")
Weight	206 g (7.3 oz)
Enclosure material	Polycarbonate

### Hardware

Management interface	Ethernet In-Band
Networking interface	(5) 1/2.5 GbE RJ45 ports
Total non-blocking throughput	12.5 Gbps
Switching capacity	25 Gbps
Forwarding rate	18.6 Mpps
Power method	(1) AC power adapter, 5V DC, 1A (1) PoE (PairA 1, 2+; 3, 6-)(PairB 4, 5+; 7, 8-)
Power supply	External AC/DC adapter UniFi PoE switch
Supported voltage range	AC/DC input: 5V DC PoE input: 44—57V DC
Max. power consumption	AC/DC input: 5W PoE input: 6.4W
Button	Factory reset
Ambient operating temperature	-20 to 45° C (-4 to 113° F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

### Switching Features

Layer 2 features	STP / RSTP with priorities and port-level disable Port isolation Storm control
------------------	--

Port mirroring  
Multicast / broadcast rate limiting  
Flow control  
Jumbo frames  
Egress rate limit

Layer 3 features –

**LEDs**

System  
(1) Blue/white: power  
Blinking white: bootup in progress  
Blinking blue: firmware upgrading  
Steady white: factory defaults; unit is awaiting adoption  
Steady blue: unit is adopted

Ethernet (5) Green: link/activity

**Application Requirements**

UniFi Network Version 8.4.62 and later

